

Blaster Checklist

Daily Checklist	Notes
Check to see if air is on feeding dust collector	
Purge dust filters by setting min and max to zero for 10 mins	
Remove trash from grating	
Check DP on dust collector manometer	Replace filters if reading will not go below 2
Check hoses, couplings, and signs of wear and tear or holes	Replace as needed
Check green light on CO monitor	If light is not green do not blast report to manager
Check air hood for signs of wear or broken components	Fix before beginning blast
Check level of media in blast pot	Do not overfill, keep at or below the plunger guide
Check the drum below the dust collector. Empty if more than ½ full.	Do not allow it to fill more than ½ full. Too heavy
Open door on reclaimer and check for trash	Remove trash before operating

Weekly Checklist	Notes
Sweep up entire floor and push all through the grating for reclaim	This will keep contaminants from building up.
Check nozzle orifice (¼" new). It can wear up to one size.	If nozzle size exceeds 7/16" then replace
Check drum wear and tear	Order new drum as needed
Check inner & outer replacement levels	Order if less than one full pack on hand

Blaster Checklist

Monthly Checklist	Notes
Blow out lights	Replace as needed, last replaced _____

Quarterly Checklist	Notes
Replace personal air filter cartridge	Last replaced _____
Turn recovery hose 180 degrees	

Annual Checklist	Notes
Replace plunger, metering tube, exhaust valve restrictor.	Last replaced _____
Replace filters	